

oH-Ho NXT P 30W | 30W

Product Reference

Environment Indoor

Installation Ceiling Suspended

Construction & Materials

Housing Spun Aluminium

Primary Lens -

Primary Reflector -

Secondary Reflector -

Body Finish White,Black,Custom

Diffuser Premium high-transmission opal

Antiglare Baffle -

Thermal Management

Heat Sink Material Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction General Diffuse

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Integral

LED Power Watts 23.3W

System Power Watts 26.8W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.95

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	oH-Ho NXT P 30W	30W	WW27K	CRI80/90	128°	SWH	

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT		CRI	ANGLE	FINISH		CONTROL
oH-Ho NXT P 30W	30W	1930	72	2700K	WW27K	CRI80/90	128°	White	SWH	
		2010	75	3000K	WW30K			Black	SBL	
		2144	80	4000K	NW40K			Custom	CSM	
		2198	82	5700K	CW57K					
oH-Ho NXT P 30W	30W			WW27K		CRI80/90	128°	SWH		



Light Distribution

LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80/90

Led Type SMD mid power

LED Fitted Samsung Mid power LED array 32V-36Vdc/700mA

Controls

Standard Switchable On/Off

Optional PDIM,DDIM,CASAMBI,Non Dimmable