











Dimmable

CRI 90

iFlex Grazer | 25W/MTR

Product Reference


Environment Outdoor

Installation Ceiling Surface, Floor Surface, Wall Surface

Construction & Materials

Housing Primary Lens PMMA
Primary Reflector Secondary Reflector Body Finish White
Diffuser Antiglare Baffle -





Thermal Management

Heat Sink Material -

Cooling Technique Passive Cooling


Optical System

Beam Direction -

Tilt -

Swivel -

Light Distribution



Electrical System

Driven with Constant Voltage Driver
Input Voltage/Hz Control Gear Mounting Remote
LED Power Watts 25W/Mtr
System Power Watts Operating Voltage Vin Power Factor p.f. -

LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD high power

LED Fitted -

Controls

Standard Switchable On/Off
Optional DDIM,BTTM,CASAMBI

Ordering Details

Code Example: Name Watt CCT CRI Angle Finish Control

| Flex Grazer | 25W/MTR | CRI80 | 25°x50° | SWH | On/Off |

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	ССТ	CRI	ANGLE	FINISH	CONTROL	
iFlex Grazer	25W/MTR	2000	80	3000K	CRI80	25°x50°	White SW F	Non Dimmable	On/Off
					CRI90		3 3 5 6 8 8 8	Dali Dimmable	DDIM
								Bluetooth Dimmable	BTTM
								Casambi	СВТМ
iFlex Grazer	25W/MTR				CRI80	25°x50°	SWH	On/Off	