

Linescape 1708 | 15W

Product Reference

Environment Indoor
 Installation Ceiling Recess

Construction & Materials

Housing Aluminium
 Primary Lens -
 Primary Reflector -
 Secondary Reflector -
 Body Finish Anodised Aluminium
 Diffuser Opal PC
 Antiglare Baffle -

Thermal Management


Heat Sink Material Aluminium
 Cooling Technique Passive Cooling

Optical System


Beam Direction Fixed
 Tilt No
 Swivel No

Electrical System

Driven with Constant Voltage Driver
 Input Voltage/Hz 220V- 240V/50-60Hz
 Control Gear Included
 Mounting Remote
 LED Power Watts 14.4
 System Power Watts -
 Operating Voltage Vin 220V- 240V/50-60Hz
 Power Factor p.f. >0.95



Light Distribution



LED Technology

Binning 3 Step MacAdam
 LED Life Time @ L80/B10 >50000 hours
 Colour Rendering (CRI) CRI80
 Led Type SMD mid power
 LED Fitted SMD mid power

Controls

Standard Switchable On/Off
 Optional DDIM

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Linescape 1708	15W	WW27K	CRI80	110°	AL	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL
Linescape 1708	15W	720	50	2700K	WW27K	110°	Anodised Aluminium	AL
		749	52	3000K	WW30K			
		792	55	4000K	NW40K			
		821	57	5700K	CW57K			
Linescape 1708	15W			WW27K	CRI80	110°	AL	On/Off