

# Linescape 1408 | 15W

## Product Reference

Environment Indoor  
 Installation Ceiling Recess

## Construction & Materials

Housing Aluminium  
 Primary Lens -  
 Primary Reflector -  
 Secondary Reflector -  
 Body Finish Anodised Aluminium  
 Diffuser Opal PC  
 Antiglare Baffle -

## Thermal Management


Heat Sink Material Aluminium  
 Cooling Technique Passive Cooling

## Optical System


Beam Direction Fixed  
 Tilt No  
 Swivel No

## Electrical System

Driven with Constant Voltage Driver  
 Input Voltage/Hz 220V- 240V/50-60Hz  
 Control Gear Included  
 Mounting Remote  
 LED Power Watts 14.4  
 System Power Watts -  
 Operating Voltage Vin 220V- 240V/50-60Hz  
 Power Factor p.f. >0.95



## Light Distribution



## LED Technology

Binning 3 Step MacAdam  
 LED Life Time @ L80/B10 >50000 hours  
 Colour Rendering (CRI) CRI80  
 Led Type SMD mid power  
 LED Fitted SMD mid power

## Controls

Standard Switchable On/Off  
 Optional DDIM

## Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	<b>Linescape 1408</b>	<b>15W</b>	<b>WW27K</b>	<b>CRI80</b>	<b>110°</b>	<b>AL</b>	<b>On/Off</b>

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL
<b>Linescape 1408</b>	<b>15W</b>	720	50	2700K <b>WW27K</b>	<b>CRI80</b>	<b>110°</b>	Anodised Aluminium <b>AL</b>	Non Dimmable <b>On/Off</b>
		749	52	3000K <b>WW30K</b>				Dali Dimmable <b>DDIM</b>
		792	55	4000K <b>NW40K</b>				
		821	57	5700K <b>CW57K</b>				
<b>Linescape 1408</b>	<b>15W</b>			<b>WW27K</b>	<b>CRI80</b>	<b>110°</b>	<b>AL</b>	<b>On/off</b>