

# Dark Knight L 2Way | 2X15W

## Product Reference

Environment Indoor

Installation Ceiling Recess

## Construction & Materials

Housing Die Cast Aluminium

Primary Lens -

Primary Reflector PC metallised

Secondary Reflector Black Raster - ABS

Body Finish White,Black,Custom

Diffuser -

Antiglare Baffle -

## Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

## Optical System

Beam Direction Fixed

Tilt No

Swivel No

## Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included



Mounting Remote

LED Power Watts 2x12.7W


System Power Watts 2x14.6W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.95



## Light Distribution



## LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted CREE COB LED 36Vdc/350mA

## Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable

## Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	<b>Dark Knight L 2Way</b>	<b>2X15W</b>	<b>WW27K</b>	<b>CRI80</b>	<b>22°(SS)</b>	<b>SWH</b>	<b>On/Off</b>

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL
<b>Dark Knight L 2Way</b>	<b>2X15W</b>	2x1153	79	2700K	<b>WW27K</b>	<b>CRI80</b>	22°(SS) <b>28°(MD)</b>	Non Dimmable <b>On/Off</b>
		2x1183	81	3000K	<b>WW30K</b>	CRI90	28°(MD)	Phase Dimmable <b>PDIM</b>
		2x1270	87	4000K	<b>NW40K</b>		52°(WD)	Dali Dimmable <b>DDIM</b>
		2x1285	88	5700K	<b>CW57K</b>			Bluetooth Dimmable <b>BTTM</b>
				2700K-5700K	<b>TW</b>			Casambi <b>CBTM</b>
<b>Dark Knight L 2Way</b>	<b>2X15W</b>			<b>WW27K</b>	<b>CRI80</b>	<b>22°(SS)</b>	<b>SWH</b>	<b>On/Off</b>

