

Rio V2 | 10W

Product Reference

Environment Indoor

Installation Ceiling Recess

Construction & Materials

Housing Die Cast Aluminium

Primary Lens PMMA

Primary Reflector PC metallised

Secondary Reflector Anodised

Body Finish White,Black,Custom

Diffuser -

Antiglare Baffle -

Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Fixed

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included


Mounting Remote

LED Power Watts 8.5W


System Power Watts 9.8W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.95



Light Distribution



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted CREE COB LED 36Vdc/250mA

Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTDM,CASAMBI,Non Dimmable

Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Rio V2	10W	WW27K	CRI80	22°(SS)	SWH	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT		CRI	ANGLE		FINISH		CONTROL	
Rio V2	10W	637	65	2700K	WW27K	CRI80	22°(SS)	24°(MD)	White	SWH	Non Dimmable	On/Off
		666	68	3000K	WW30K	CRI90	24°(MD)		Black	SBL	Phase Dimmable	PDIM
		696	71	4000K	NW40K		33°(WD)		Custom	CSM	Dali Dimmable	DDIM
		715	73	5700K	CW57K						Bluetooth Dimmable	BTDM
				2700K-5700K	TW						Casambi	CBTM
				Warm to Dim	W2D							
Rio V2	10W			WW27K		CRI80	22°(SS)		SWH		On/Off	