

## Go Pro 70 TT | 24W

### Product Reference

Environment Indoor

Installation Ceiling Recess

### Construction & Materials

Housing Die Cast Aluminium

Primary Lens PMMA

Primary Reflector -

Secondary Reflector Anodised

Body Finish White,Black

Diffuser -

Antiglare Baffle -

### Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

### Optical System

Beam Direction Fixed

Tilt No

Swivel No

### Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included


Mounting Remote

LED Power Watts 19.6W


System Power Watts 22.5W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.95



### Light Distribution



### LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted CREE COB LED 36Vdc/600mA

### Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable

### Ordering Details

| Code Example: | Name                | Watt       | CCT          | CRI          | Angle          | Finish     | Control       |
|---------------|---------------------|------------|--------------|--------------|----------------|------------|---------------|
|               | <b>Go Pro 70 TT</b> | <b>24W</b> | <b>WW27K</b> | <b>CRI80</b> | <b>21°(ss)</b> | <b>SWH</b> | <b>On/Off</b> |

Select one from each column with highlighted values to create the ordering code

| NAME                | WATT       | LUMEN | EFFICACY | CCT          |              | CRI          | ANGLE          | FINISH     |            | CONTROL            |               |
|---------------------|------------|-------|----------|--------------|--------------|--------------|----------------|------------|------------|--------------------|---------------|
| <b>Go Pro 70 TT</b> | <b>24W</b> | 2138  | 95       | 2700K        | <b>WW27K</b> | <b>CRI80</b> | 21°(SS)        | White      | <b>SWH</b> | Non Dimmable       | <b>On/Off</b> |
|                     |            | 2205  | 98       | 3000K        | <b>WW30K</b> | CRI90        | 40°(MD)        | Black      | <b>SBL</b> | Phase Dimmable     | <b>PDIM</b>   |
|                     |            | 2318  | 103      | 4000K        | <b>NW40K</b> |              | 52°(WD)        |            |            | Dali Dimmable      | <b>DDIM</b>   |
|                     |            | 2363  | 105      | 5700K        | <b>CW57K</b> |              |                |            |            | Bluetooth Dimmable | <b>BTTM</b>   |
|                     |            |       |          | 2700K-5700K  | <b>TW</b>    |              |                |            |            | Casambi            | <b>CBTM</b>   |
|                     |            |       |          | Warm to Dim  | <b>W2D</b>   |              |                |            |            |                    |               |
| <b>Go Pro 70 TT</b> | <b>24W</b> |       |          | <b>WW27K</b> |              | <b>CRI80</b> | <b>21°(ss)</b> | <b>SWH</b> |            | <b>On/Off</b>      |               |