

Go Pro 35 M | 5W

Product Reference

Environment Indoor

Installation Ceiling Recess

Construction & Materials

Housing Die Cast Aluminium

Primary Lens PMMA

Primary Reflector -

Secondary Reflector Anodised

Body Finish White,Black

Diffuser -

Antiglare Baffle -

Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Adjustable

Tilt Yes

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included


Mounting Remote

LED Power Watts 3.4W


System Power Watts 4.2W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.5



Light Distribution



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted CREE COB LED 9Vdc/350mA

Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable

Ordering Details

| Code Example: | Name | Watt | CCT | CRI | Angle | Finish | Control |
|---------------|-------------|------|-------|-------|---------|--------|---------|
| | Go Pro 35 M | 5W | WW27K | CRI80 | 24°(MD) | SWH | On/Off |

Select one from each column with highlighted values to create the ordering code

| NAME | WATT | LUMEN | EFFICACY | CCT | CRI | ANGLE | FINISH | CONTROL | |
|-------------|------|-------|----------|-------|-------|-----------------|----------|-----------|---------------------|
| Go Pro 35 M | 5W | 420 | 100 | 2700K | WW27K | CRI80 | 24°(MD) | White SWH | Non Dimmable On/Off |
| | | 433 | 103 | 3000K | WW30K | CRI90 | 36°(WD) | Black SBL | Phase Dimmable PDIM |
| | | 454 | 108 | 4000K | NW40K | | 52°(VWD) | | Dali Dimmable DDIM |
| | | 466 | 111 | 5700K | CW57K | | | | Casambi CBTM |
| | | | | | | Warm to Dim W2D | | | |
| Go Pro 35 M | 5W | | | WW27K | CRI80 | 24°(MD) | SWH | On/Off | |