

Go Pro 35 S | 5W

Product Reference

Environment Indoor

Installation Ceiling Surface

Construction & Materials

Housing Die Cast Aluminium

Primary Lens PMMA

Primary Reflector -

Secondary Reflector Anodised

Body Finish White,Black,Custom

Diffuser -

Antiglare Baffle -

Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

Optical System

Beam Direction Fixed

Tilt No

Swivel No

Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included

Mounting Integral

LED Power Watts 3.4W

System Power Watts 4.2W

Operating Voltage Vin 220-240 Vac


Power Factor p.f. > 0.5

Ordering Details


Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	Go Pro 35 S	5W	WW27K	CRI80	24°(MD)	SWH	On/Off

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL	
Go Pro 35 S	5W	420	100	2700K	WW27K	CRI80	24°(MD)	White SWH	Non Dimmable On/Off
		433	103	3000K	WW30K	CRI90	36°(WD)	Black SBL	
		454	108	4000K	NW40K		52°(VWD)	Custom CSM	
		466	111	5700K	CW57K				
Go Pro 35 S	5W			WW27K	CRI80	24°(MD)	SWH	On/Off	



Light Distribution



LED Technology

Binning 3 Step MacAdam

LED Life Time @ L80/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type COB

LED Fitted CREE COB LED 9Vdc/350mA

Controls

Standard Switchable On/Off

Optional Non Dimmable