

## Rad | 12W

### Product Reference

Environment Indoor

Installation Ceiling Recess

### Construction & Materials

Housing Die Cast Aluminium

Primary Lens -

Primary Reflector White Optics

Secondary Reflector -

Body Finish White

Diffuser Premium high-transmission opal

Antiglare Baffle -

### Thermal Management

Heat Sink Material Die cast Aluminium

Cooling Technique Passive Cooling

### Optical System

Beam Direction General Diffuse

Tilt No

Swivel No

### Electrical System

Driven with Constant Current Driver

Input Voltage/Hz 220V- 240V/50-60Hz

Control Gear Included


Mounting Remote

LED Power Watts 10.3W


System Power Watts 11.8W

Operating Voltage Vin 220-240 Vac

Power Factor p.f. > 0.95



### Light Distribution



### LED Technology

Binning 3 Step MacAdam

LED Life Time @ L70/B10 >50000 hours

Colour Rendering (CRI) CRI80,CRI90

Led Type SMD mid power

LED Fitted Samsung Mid power LED array 32V-36Vdc/300mA

### Controls

Standard Switchable On/Off

Optional PDIM,DDIM,BTTM,CASAMBI,Non Dimmable

### Ordering Details

Code Example:	Name	Watt	CCT	CRI	Angle	Finish	Control
	<b>Rad</b>	<b>12W</b>	<b>WW27K</b>	<b>CRI80</b>	<b>78°</b>	<b>SWH</b>	<b>On/Off</b>

Select one from each column with highlighted values to create the ordering code

NAME	WATT	LUMEN	EFFICACY	CCT	CRI	ANGLE	FINISH	CONTROL	
<b>Rad</b>	<b>12W</b>	1121	95	2700K	<b>WW27K</b>	<b>78°</b>	White <b>SWH</b>	Non Dimmable	<b>On/Off</b>
		1156	98	3000K	<b>WW30K</b>			Phase Dimmable	<b>PDIM</b>
		1227	104	4000K	<b>NW40K</b>			Dali Dimmable	<b>DDIM</b>
		1251	106	5700K	<b>CW57K</b>			Bluetooth Dimmable	<b>BTTM</b>
								Casambi	<b>CBTM</b>
<b>Rad</b>	<b>12W</b>			<b>WW27K</b>	<b>CRI80</b>	<b>78°</b>	<b>SWH</b>	<b>On/Off</b>	